

TYRES

Product group	Tyres	
Item number	15222182	
Valid tyre size	11.2 - 24	
LI / SI / PR	125 A2 / 119 A8, 10 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestry 356	



Notes and features

- The Alliance Forestry 356 is a modern bias tyre for highpower tractors in forestry applications or for heavy-duty operations in agriculture.
- It is also suitable for agricultural vehicles used on construction sites.
- The tyre is characterised by high traction, low slip and low fuel consumption.
- Due to its strong nylon casing with steel belts, high undertread gauge, reinforced sidewalls and a sturdy rubber compound, the tyre is extremely robust and durable.
- The non-skid tread pattern promises high traction, even on compacted or wet surfaces.



Technical Informations

Item number	15222182
EAN	7291050044363
Valid tyre size	11.2 - 24
LI / SI / PR	125 A2 / 119 A8, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	48,99
Recommended rim size	10
Maximum air pressure [bar].	3,00
Section width (mm)	290
Outer diameter of tyre [mm].	1112
Stat. radius (SLR) [mm]	518
Rolling circumference [mm].	3346
Tread depth (mm)	39,0
Number of lugs	19x2
Lug width (mm)	44-33
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A2	1650	10		3,00	
119 A8	1360	40		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.