

TYRES

Product group	Tyres
Item number	15222191
Valid tyre size	11.2 - 24
LI / SI / PR	116 A8, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	FarmPRO 324



Notes and features

- The Alliance FarmPro 324 has a modern 45 degree lug angle design, suitable for field and road applications.
- In field use, the tyre is characterised by very good traction.
- The revised, new-look tread pattern provides excellent self-cleaning properties.
- Its particularly resistant rubber compound prevents the enlargement of minor punctures.
- The complete R-1 range is available with this tread pattern.



Technical Informations

Item number	15222191
EAN	8903635017660
Valid tyre size	11.2 - 24
LI / SI / PR	116 A8, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	FarmPRO 324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	38,88
Recommended rim size	10
Maximum air pressure [bar].	2,40
Section width (mm)	284
Outer diameter of tyre [mm].	1105
Stat. radius (SLR) [mm]	512
Rolling circumference [mm].	3314
Tread depth (mm)	33,0
Number of lugs	18x2
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A8	1250	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.