

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 15222197 |
| Valid tyre size | 12.4 - 24 |
| LI / SI / PR | 129 A8, 12 PR |
| TL/TT | TT |
| Brand | Alliance |
| Tread pattern | 357 |



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

Notes and features

- Agricultural bias tyre with reinforced lugs for heavy-duty operations on rear wheel tractors.
- Double angled 45° lugs for good self-cleaning properties and massive traction, even on slopes.
- Wide centre lugs for good ride comfort on the road.
- Rugged nylon casing offers operational reliability.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15222197 |
| EAN | 8903635001096 |
| Valid tyre size | 12.4 - 24 |
| LI / SI / PR | 129 A8, 12 PR |
| TL/TT | TT |
| Brand | Alliance |
| Tread pattern | 357 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 43,94 |
| Recommended rim size | 11 |
| Permitted rim size | 10 |
| Maximum air pressure [bar]. | 3,50 |
| Section width (mm) | 315 |
| Outer diameter of tyre [mm]. | 1160 |
| Stat. radius (SLR) [mm] | 533 |
| Rolling circumference [mm]. | 3461 |
| Tread depth (mm) | 34,0 |
| Number of lugs | 18x2 |
| Lug width (mm) | 57-44 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 129 A8 | 1850 | 40 | | 3,50 | |