Bohnenkamp Moving Professionals

19.09.2024

TYRES

Product group	Tyres	
Item number	15222198	
Valid tyre size	13.6 - 24	
LI / SI / PR	136 A2 / 128 A8, 10 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestry 356	





Notes and features

- The Alliance Forestry 356 is a modern bias tyre for highpower tractors in forestry applications or for heavy-duty operations in agriculture.
- It is also suitable for agricultural vehicles used on construction sites.
- The tyre is characterised by high traction, low slip and low fuel consumption.
- Due to its strong nylon casing with steel belts, high undertread gauge, reinforced sidewalls and a sturdy rubber compound, the tyre is extremely robust and durable.
- The non-skid tread pattern promises high traction, even on compacted or wet surfaces.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15222198
EAN	7291050043922
Valid tyre size	13.6 - 24
LI / SI / PR	136 A2 / 128 A8, 10 PR
	TL
Brand	Alliance
Tread pattern	Forestry 356
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	76,66
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	2,50
Section width (mm)	345
Outer diameter of tyre [mm].	1190
Stat. radius (SLR) [mm]	542
Rolling circumference [mm].	3603
Tread depth (mm)	42,0
Number of lugs	18x2
Lug width (mm)	31
E-Ready	No

19.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A2	2240	10		2,50	
128 A8	1800	40		2,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.