Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15222206	
Valid tyre size	14.9 - 24	
LI / SI / PR	123 A8, 6 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	329	





Notes and features

- Popular golf tread pattern for towed vehicles. .
- Gentle on the soil.

• Also for tractors and road construction.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15222206
EAN	8903635001911
Valid tyre size	14.9 - 24
LI / SI / PR	123 A8, 6 PR
TL/TT	TL
Brand	Alliance
Tread pattern	329
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	55,90
Recommended rim size	W13
Permitted rim size	W12
Maximum air pressure [bar].	1,40
Section width (mm)	394
Outer diameter of tyre [mm].	1241
Stat. radius (SLR) [mm]	569
Rolling circumference [mm].	3698
Tread depth (mm)	24,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
123 A8	1550	40		1,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.