

TYRES

Product group	Tyres	
Item number	15222212	
Valid tyre size	14.9 / 13 - 24	
LI / SI / PR	145 A8, 12 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	533	



Notes and features

- The Alliance 533 is an industrial and construction tyre for wheel loaders and backhoes.
- Its strong nylon casing offers the best conditions for offroad use on construction sites.
- Its tread pattern provides good traction, braking power and high mileage when used on roads.
- The tyre can also be used on municipal tractors and agricultural vehicles.



Technical Informations

Item number	15222212
EAN	8903635002062
Valid tyre size	14.9 / 13 - 24
LI / SI / PR	145 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	533
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	66,51
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	2,90
Section width (mm)	378
Outer diameter of tyre [mm].	1241
Stat. radius (SLR) [mm]	560
Rolling circumference [mm].	3661
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		2,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.