

## TYRES

|                 |              |
|-----------------|--------------|
| Product group   | Tyres        |
| Item number     | 15222213     |
| Valid tyre size | 14.9 - 24    |
| LI / SI / PR    | 128 A8, 8 PR |
| TL/TT           | TT           |
| Brand           | Alliance     |
| Tread pattern   | FarmPRO 324  |



## Notes and features

- The Alliance FarmPro 324 has a modern 45 degree lug angle design, suitable for field and road applications.
- In field use, the tyre is characterised by very good traction.
- The revised, new-look tread pattern provides excellent self-cleaning properties.
- Its particularly resistant rubber compound prevents the enlargement of minor punctures.
- The complete R-1 range is available with this tread pattern.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 15222213      |
| EAN                          | 8903635014737 |
| Valid tyre size              | 14.9 - 24     |
| LI / SI / PR                 | 128 A8, 8 PR  |
| TL/TT                        | TT            |
| Brand                        | Alliance      |
| Tread pattern                | FarmPRO 324   |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 54,45         |
| Recommended rim size         | 13            |
| Maximum air pressure [bar].  | 1,80          |
| Section width (mm)           | 378           |
| Outer diameter of tyre [mm]. | 1265          |
| Stat. radius (SLR) [mm]      | 585           |
| Rolling circumference [mm].  | 3801          |
| Tread depth (mm)             | 32,0          |
| Number of lugs               | 18x2          |
| Guarantee period             | 7 years       |
| E-Ready                      | No            |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 128 A8 | 1800               | 40           |               | 1,80                     |              |