

TYRES

Product group	Tyres
Item number	15222262
Valid tyre size	16.9 - 24
LI / SI / PR	133 A8, 8 PR
TL/TT	TL
Brand	Alliance
Tread pattern	329





Notes and features

- Popular golf tread pattern for towed vehicles.
- Gentle on the soil.

• Also for tractors and road construction.



Technical Informations

Item number	15222262
EAN	8903635001942
Valid tyre size	16.9 - 24
LI / SI / PR	133 A8, 8 PR
TL/TT	TL
Brand	Alliance
Tread pattern	329
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	68,54
Recommended rim size	15
Maximum air pressure [bar].	1,70
Section width (mm)	442
Outer diameter of tyre [mm].	1309
Stat. radius (SLR) [mm]	579
Rolling circumference [mm].	3814
Tread depth (mm)	24,0
E-Ready	No

Load capacity

Ind	lex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133	A8	2060	40		1,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.