

TYRES

Product group	Tyres
Item number	15222268
Valid tyre size	15.5 / 80 - 24
LI / SI / PR	157 A6 / 154 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222268
EAN	8903635000815
Valid tyre size	15.5 / 80 - 24
LI / SI / PR	157 A6 / 154 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	65,12
Recommended rim size	12
Permitted rim size	14
Maximum air pressure [bar].	3,00
Section width (mm)	384
Outer diameter of tyre [mm].	1262
Stat. radius (SLR) [mm]	566
Rolling circumference [mm].	3786
Tread depth (mm)	36,5
Number of lugs	18x2
Lug width (mm)	52-34
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A6	4125	30		3,00	
154 A8	3750	40		3,00	