

TYRES

Product group	Tyres
Item number	15222273
Valid tyre size	15.5 / 80 - 24
LI / SI / PR	157 A6 / 154 A8, 12 PR
TL/TT	TT
Brand	Alliance
Tread pattern	533



Notes and features

- The Alliance 533 is an industrial and construction tyre for wheel loaders and backhoes.
- Its strong nylon casing offers the best conditions for off-road use on construction sites.
- Its tread pattern provides good traction, braking power and high mileage when used on roads.
- The tyre can also be used on municipal tractors and agricultural vehicles.

Technical Informations

Item number	15222273
EAN	8903635001607
Valid tyre size	15.5 / 80 - 24
LI / SI / PR	157 A6 / 154 A8, 12 PR
TL/TT	TT
Brand	Alliance
Tread pattern	533
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	68,46
Recommended rim size	12
Permitted rim size	13, 14
Maximum air pressure [bar].	3,00
Section width (mm)	394
Outer diameter of tyre [mm].	1262
Stat. radius (SLR) [mm]	552
Rolling circumference [mm].	3652
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A6	4125	30		3,00	
154 A8	3750	40		3,00	