

TYRES

Product group	Tyres
Item number	15222280
Valid tyre size	17.5 L - 24
LI / SI / PR	144 A8, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	533



Notes and features

- The Alliance 533 is an industrial and construction tyre for wheel loaders and backhoes.
- Its strong nylon casing offers the best conditions for off-road use on construction sites.
- Its tread pattern provides good traction, braking power and high mileage when used on roads.
- The tyre can also be used on municipal tractors and agricultural vehicles.

Technical Informations

Item number	15222280
EAN	8903635001218
Valid tyre size	17.5 L - 24
LI / SI / PR	144 A8, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	533
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	70,40
Recommended rim size	W15L
Permitted rim size	W14L
Maximum air pressure [bar].	2,20
Section width (mm)	444
Outer diameter of tyre [mm].	1240
Stat. radius (SLR) [mm]	551
Rolling circumference [mm].	3623
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		2,20	