Bohnenkamp Moving Professionals

19.09.2024

TYRES

Product group	Tyres	
Item number	15222295	
Valid tyre size	54 x 37.00 - 25	
LI / SI / PR	166 A2 / 158 A8, 12 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 344	





Notes and features

- The Alliance Forestar 344 is a powerful forestry tyre for CTL machines.
- The steel-reinforced nylon casing, the special rubber compound, as well as the reinforced sidewalls, protect the tyre against punctures.
- The traction tread pattern with low-angled lugs provides excellent grip and good self-cleaning thanks to wide gaps between the lugs.
- Due to the close spacing of the lugs in the centre of the tread, the rolling resistance can be reduced on hard surfaces.
- Matching chains and ribbons are available on the market.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	1522295
EAN	7291050061841
Valid tyre size	54 x 37.00 - 25
LI / SI / PR	166 A2 / 158 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	303,19
Recommended rim size	32
Permitted rim size	32
Maximum air pressure [bar].	2,40
Section width (mm)	920
Outer diameter of tyre [mm].	1435
Stat. radius (SLR) [mm]	672
Rolling circumference [mm].	4335
Tread depth (mm)	43,0
Tyre capacity 75% [ltr.]	802
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A2	5300	10		2,40	
158 A8	4250	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.