

TYRES

Product group	Tyres	
Item number	15222360	
Valid tyre size	23.1 - 26	
LI / SI / PR	153 A8, 12 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	329	





Notes and features

- Popular golf tread pattern for towed vehicles.
- Gentle on the soil.

• Also for tractors and road construction.



Technical Informations

Item number	15222360
EAN	8903635000891
Valid tyre size	23.1 - 26
LI / SI / PR	153 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	329
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	121,20
Recommended rim size	DW20
Maximum air pressure [bar].	1,70
Section width (mm)	587
Outer diameter of tyre [mm].	1560
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4545
Tread depth (mm)	23,0
Lug width (mm)	91
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A8	3650	40		1,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.