

TYRES

Product group	Tyres
Item number	15222376
Valid tyre size	23.1 - 26
LI / SI / PR	159 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO 324



Notes and features

- The Alliance FarmPro 324 has a modern 45 degree lug angle design, suitable for field and road applications.
- Its particularly resistant rubber compound prevents the enlargement of minor punctures.
- In field use, the tyre is characterised by very good traction.
- The complete R-1 range is available with this tread pattern.
- The revised, new-look tread pattern provides excellent self-cleaning properties.

Technical Informations

Item number	15222376
EAN	8903635027461
Valid tyre size	23.1 - 26
LI / SI / PR	159 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO 324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	135,00
Recommended rim size	DW20
Maximum air pressure [bar].	2,30
Section width (mm)	587
Outer diameter of tyre [mm].	1600
Stat. radius (SLR) [mm]	720
Rolling circumference [mm].	4769
Tread depth (mm)	43,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	456.15
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		2,30	