

TYRES

Product group	Tyres
Item number	15222387
Valid tyre size	28 L - 26
LI / SI / PR	184 A2 / 173 A6, 26 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 345



Notes and features

- The Alliance Forestar 345 was developed for use on heavy forestry machines and logging equipment operating in challenging conditions.
- The tyre provides high traction and low slip, even without chains.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls, the tyre is very tough and durable.
- Thanks to its high lugs and especially hard-wearing rubber compound, the tyre is optimally suited to demanding forest applications.
- It is the ideal tyre for skidders.

Technical Informations

Item number	15222387
EAN	7291050062534
Valid tyre size	28 L - 26
LI / SI / PR	184 A2 / 173 A6, 26 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 345
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	305,00
Recommended rim size	25
Maximum air pressure [bar].	3,90
Section width (mm)	715
Outer diameter of tyre [mm].	1638
Stat. radius (SLR) [mm]	746
Rolling circumference [mm].	4861
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A2	9000	10		3,90	
173 A6	6500	30		3,60	