

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15222388 |
| Valid tyre size | 28 L - 26 |
| LI / SI / PR | 177 A2 / 165 A6, 20 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Forestar 345 |



Notes and features

- The Alliance Forestar 345 was developed for use on heavy forestry machines and logging equipment operating in challenging conditions.
- The tyre provides high traction and low slip, even without chains.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls, the tyre is very tough and durable.
- Thanks to its high lugs and especially hard-wearing rubber compound, the tyre is optimally suited to demanding forest applications.
- It is the ideal tyre for skidders.

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15222388 |
| EAN | 7291050058131 |
| Valid tyre size | 28 L - 26 |
| LI / SI / PR | 177 A2 / 165 A6, 20 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Forestar 345 |
| TRA Code | LS-2 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 292,04 |
| Recommended rim size | 25 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 715 |
| Outer diameter of tyre [mm]. | 1638 |
| Stat. radius (SLR) [mm] | 746 |
| Rolling circumference [mm]. | 4861 |
| Tread depth (mm) | 50,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 177 A2 | 7300 | 10 | | 2,40 | |
| 165 A6 | 5150 | 30 | | 2,40 | |