# Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15222391	
Valid tyre size	28L - 26	
LI / SI / PR	173 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	330	

05.02.2025





### Notes and features

- Popular golf tread pattern for towed vehicles.
- Gentle on the soil.

• Also for tractors and road construction.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	15222391
EAN	8903635000952
Valid tyre size	28L - 26
LI / SI / PR	173 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	330
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	181,00
Recommended rim size	25
Maximum air pressure [bar].	2,20
Section width (mm)	714
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	702
Rolling circumference [mm].	4627
Tread depth (mm)	28,0
Lug width (mm)	90
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		2,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.