

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 15222434 |
| Valid tyre size | 12.4 - 28 |
| LI / SI / PR | 125 A8, 12 PR |
| TL/TT | TT |
| Brand | Alliance |
| Tread pattern | 324 |



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15222434 |
| EAN | 8903635005377 |
| Valid tyre size | 12.4 - 28 |
| LI / SI / PR | 125 A8, 12 PR |
| TL/TT | TT |
| Brand | Alliance |
| Tread pattern | 324 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 53,86 |
| Recommended rim size | 11 |
| Permitted rim size | 10 |
| Maximum air pressure [bar]. | 2,50 |
| Section width (mm) | 315 |
| Outer diameter of tyre [mm]. | 1260 |
| Stat. radius (SLR) [mm] | 583 |
| Rolling circumference [mm]. | 3776 |
| Tread depth (mm) | 36,5 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 125 A8 | 1650 | 40 | | 2,50 | |