

TYRES

Product group	Tyres	
Item number	15222435	
Valid tyre size	12.4 - 28	
LI / SI / PR	123 A8, 8 PR	
TL/TT	тт	
Brand	Alliance	
Tread pattern	FarmPRO 324	



Notes and features

- The Alliance FarmPro 324 has a modern 45 degree lug angle design, suitable for field and road applications.
- In field use, the tyre is characterised by very good traction.
- The revised, new-look tread pattern provides excellent self-cleaning properties.
- Its particularly resistant rubber compound prevents the enlargement of minor punctures.
- The complete R-1 range is available with this tread pattern.



Technical Informations

Item number	15222435
item number	
EAN	8903635013778
Valid tyre size	12.4 - 28
LI / SI / PR	123 A8, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	FarmPRO 324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	45,04
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	2,30
Section width (mm)	315
Outer diameter of tyre [mm].	1260
Stat. radius (SLR) [mm]	583
Rolling circumference [mm].	3776
Tread depth (mm)	34,0
Number of lugs	20x2
Guarantee period	7 years
E-Ready	No

Load capacity

ı	Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
1	.23 A8	1550	40		2,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.