

TYRES

Product group	Tyres	
Item number	15222451	
Valid tyre size	13.6 - 28	
LI / SI / PR	138 A2 / 130 A8, 10 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestry 356	



Notes and features

- The Alliance Forestry 356 is a modern bias tyre for highpower tractors in forestry applications or for heavy-duty operations in agriculture.
- It is also suitable for agricultural vehicles used on construction sites.
- The tyre is characterised by high traction, low slip and low fuel consumption.
- Due to its strong nylon casing with steel belts, high undertread gauge, reinforced sidewalls and a sturdy rubber compound, the tyre is extremely robust and durable.
- The non-skid tread pattern promises high traction, even on compacted or wet surfaces.



Technical Informations

Item number	15222451
EAN	7291050044882
Valid tyre size	13.6 - 28
LI / SI / PR	138 A2 / 130 A8, 10 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 356
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	73,81
Recommended rim size	12
Maximum air pressure [bar].	2,50
Section width (mm)	345
Outer diameter of tyre [mm].	1295
Stat. radius (SLR) [mm]	595
Rolling circumference [mm].	3863
Tread depth (mm)	42,0
Lug width (mm)	48-36
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A2	2360	10		2,50	
130 A8	1900	40		2,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.