

## **TYRES**

Product group	Tyres
Item number	15222487
Valid tyre size	480 / 65 - 28
LI / SI / PR	149 A2 / 142 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360





## Notes and features

- The Alliance Forestry 360 is a forestry tyre for light forestry applications.
- Its low lug angles provide excellent traction.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls and tread pattern, the tyre is particularly robust.
- The tyre can also be used for agro-industrial applications.



## **Technical Informations**

Item number	15222487
EAN	7291050065153
Valid tyre size	480 / 65 - 28
LI / SI / PR	149 A2 / 142 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	123,22
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	2,40
Section width (mm)	460
Outer diameter of tyre [mm].	1350
Stat. radius (SLR) [mm]	634
Rolling circumference [mm].	4088
Tread depth (mm)	46,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	246
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A2	3250	10		2,40	
142 A8	2650	40		2,40	