

TYRES

Product group	Tyres
Item number	15222490
Valid tyre size	16.5 / 85 - 28
LI / SI / PR	163 A6 / 159 A8, 12 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222490
EAN	8903635000846
Valid tyre size	16.5 / 85 - 28
LI / SI / PR	163 A6 / 159 A8, 12 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	80,35
Recommended rim size	13
Permitted rim size	14, 15
Maximum air pressure [bar].	2,80
Section width (mm)	417
Outer diameter of tyre [mm].	1423
Stat. radius (SLR) [mm]	626
Rolling circumference [mm].	4130
Tread depth (mm)	31,0
Number of lugs	20x2
Lug width (mm)	33
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 A6	4875	30		2,80	
159 A8	4375	40		2,80	