

TYRES

Product group	Tyres
Item number	15222555
Valid tyre size	18.4 / 15 - 28
LI / SI / PR	157 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	533
Sonderpostenkategorie	DOT
type of damage	DOT



Notes and features

- The Alliance 533 is an industrial and construction tyre for wheel loaders and backhoes.
- Its strong nylon casing offers the best conditions for off-road use on construction sites.
- Its tread pattern provides good traction, braking power and high mileage when used on roads.
- The tyre can also be used on municipal tractors and agricultural vehicles.

Technical Informations

Item number	15222555
EAN	8903635002116
Valid tyre size	18.4 / 15 - 28
LI / SI / PR	157 A8, 12 PR
TL/TT	TL
Brand	Alliance
Tread pattern	533
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 30
Nettogewicht [kg] (gültig)	102,01
Recommended rim size	W16L
Permitted rim size	W15
Maximum air pressure [bar].	2,50
Section width (mm)	467
Outer diameter of tyre [mm].	1477
Stat. radius (SLR) [mm]	655
Rolling circumference [mm].	4310
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		2,50	