

TYRES

Product group	Tyres	
Item number	15222557	
Valid tyre size	540 / 65 - 28	
LI / SI / PR	162 A2 / 155 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestry 360	



Notes and features

- The Alliance Forestry 360 is a forestry tyre for light forestry applications.
- Its low lug angles provide excellent traction.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls and tread pattern, the tyre is particularly robust.
- The tyre can also be used for agro-industrial applications.



Technical Informations

Item number	15222557
EAN	7291050045773
Valid tyre size	540 / 65 - 28
LI / SI / PR	162 A2 / 155 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	151,47
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	3,30
Section width (mm)	520
Outer diameter of tyre [mm].	1448
Stat. radius (SLR) [mm]	668
Rolling circumference [mm].	4331
Tread depth (mm)	50,0
Number of lugs	19x2
Lug width (mm)	62-56
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A2	4750	10		3,30	
155 A8	3875	40		3,30	