

TYRES

Product group	Tyres
Item number	15222563
Valid tyre size	14.9 - 30
LI / SI / PR	132 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222563
EAN	8903635000686
Valid tyre size	14.9 - 30
LI / SI / PR	132 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,38
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	1,80
Section width (mm)	378
Outer diameter of tyre [mm].	1415
Stat. radius (SLR) [mm]	660
Rolling circumference [mm].	4261
Tread depth (mm)	37,0
Number of lugs	19x2
Lug width (mm)	37
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 A8	2000	40		1,80	