

TYRES

Product group	Tyres
Item number	15222573
Valid tyre size	420 / 85 - 30
LI / SI / PR	150 A6, 16 PR
TL/TT	TT
Brand	Alliance
Tread pattern	Forestar 345



Notes and features

- The Alliance Forestar 345 was developed for use on heavy forestry machines and logging equipment operating in challenging conditions.
- The tyre provides high traction and low slip, even without chains.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls, the tyre is very tough and durable.
- Thanks to its high lugs and especially hard-wearing rubber compound, the tyre is optimally suited to demanding forest applications.
- It is the ideal tyre for skidders.

Technical Informations

Item number	15222573
EAN	8903635022114
Valid tyre size	420 / 85 - 30
Alternative size 1	16.9-30
LI / SI / PR	150 A6, 16 PR
TL/TT	TT
Brand	Alliance
Tread pattern	Forestar 345
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	151,94
Recommended rim size	15
Maximum air pressure [bar].	3,25
Section width (mm)	429
Outer diameter of tyre [mm].	1504
Stat. radius (SLR) [mm]	696
Rolling circumference [mm].	4508
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A6	3350	30		3,25	