

TYRES

Product group	Tyres
Item number	15222577
Valid tyre size	16.9 - 30
LI / SI / PR	148 A8, 14 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222577
EAN	8903635004240
Valid tyre size	16.9 - 30
LI / SI / PR	148 A8, 14 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	83,47
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	2,90
Section width (mm)	429
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	667
Rolling circumference [mm].	4369
Tread depth (mm)	38,0
Number of lugs	20x2
Lug width (mm)	32
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		2,90	