

## TYRES

Product group	Tyres
Item number	15222685
Valid tyre size	9.5 - 32
LI / SI / PR	106 A8, 6 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



## Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

## Technical Informations

Item number	15222685
EAN	8903635001553
Valid tyre size	9.5 - 32
LI / SI / PR	106 A8, 6 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	37,80
Recommended rim size	W8
Permitted rim size	W7
Maximum air pressure [bar].	2,10
Section width (mm)	241
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	587
Rolling circumference [mm].	3749
Tread depth (mm)	35,0
Number of lugs	20x2
Lug width (mm)	25
Guarantee period	7 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 A8	950	40		2,10	