

TYRES

Product group	Tyres
Item number	15222692
Valid tyre size	12.4 - 32
LI / SI / PR	125 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222692
EAN	8903635000747
Valid tyre size	12.4 - 32
LI / SI / PR	125 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	56,30
Recommended rim size	11
Permitted rim size	10
Maximum air pressure [bar].	2,20
Section width (mm)	315
Outer diameter of tyre [mm].	1360
Stat. radius (SLR) [mm]	633
Rolling circumference [mm].	4090
Tread depth (mm)	36,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A8	1650	40		2,20	