

TYRES

Product group	Tyres 15222696 24.5 - 32		
Item number			
Valid tyre size			
LI / SI / PR	181 A2 / 169 A6, 20 PR		
TL/TT	TL Alliance		
Brand			
Tread pattern	Forestar 345		





Notes and features

- The Alliance Forestar 345 was developed for use on heavy forestry machines and logging equipment operating in challenging conditions.
- The tyre provides high traction and low slip, even without chains.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls, the tyre is very tough and durable.
- Thanks to its high lugs and especially hard-wearing rubber compound, the tyre is optimally suited to demanding forest applications.
- It is the ideal tyre for skidders.



Technical Informations

Item number	15222696
EAN	7291050058148
Valid tyre size	24.5 - 32
LI / SI / PR	181 A2 / 169 A6, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 345
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	340,52
Recommended rim size	21
Maximum air pressure [bar].	2,70
Section width (mm)	622
Outer diameter of tyre [mm].	1817
Stat. radius (SLR) [mm]	833
Rolling circumference [mm].	5414
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A2	8250	10		2,70	
169 A6	5800	30		2,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.