

TYRES

Product group	Tyres
Item number	15222710
Valid tyre size	16.9 - 34
LI / SI / PR	149 A8, 14 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222710
EAN	8903635004172
Valid tyre size	16.9 - 34
LI / SI / PR	149 A8, 14 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	98,90
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	2,80
Section width (mm)	429
Outer diameter of tyre [mm].	1585
Stat. radius (SLR) [mm]	725
Rolling circumference [mm].	4716
Tread depth (mm)	37,0
Lug width (mm)	36
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		2,80	