

TYRES

Product group	Tyres	
Item number	15222745	
Valid tyre size	600 / 65 - 34	
LI / SI / PR	164 A2 / 157 A8, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 346	



Notes and features

- The Alliance Forestar 346 was developed for modern harvesters and transport equipment operating on harsh ground conditions in forestry applications.
- The tyre provides high traction, low slip and low fuel consumption.
- Its huge volume ensures low soil compaction and good ride comfort in forestry and agricultural use.
- Due to its strong nylon casing with steel belts, high undertread gauge, high and robust lugs, strong sidewalls and a sturdy rubber compound, the tyre is particularly durable.



Technical Informations

Item number	15222745
EAN	7291050015417
Valid tyre size	600 / 65 - 34
LI / SI / PR	164 A2 / 157 A8, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 346
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	221,36
Recommended rim size	20
Maximum air pressure [bar].	2,40
Section width (mm)	600
Outer diameter of tyre [mm].	1640
Stat. radius (SLR) [mm]	762
Rolling circumference [mm].	4927
Tread depth (mm)	51,0
Lug width (mm)	51-47
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A2	5000	10		2,40	
157 A8	4125	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.