Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres	
Item number	15222750	
Valid tyre size	700 / 55 - 34	
LI / SI / PR	168 A2 / 161 A8, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 346	



Notes and features

- The Alliance Forestar 346 was developed for modern harvesters and transport equipment operating on harsh ground conditions in forestry applications.
- The tyre provides high traction, low slip and low fuel consumption.
- Its huge volume ensures low soil compaction and good ride comfort in forestry and agricultural use.
- Due to its strong nylon casing with steel belts, high undertread gauge, high and robust lugs, strong sidewalls and a sturdy rubber compound, the tyre is particularly durable.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15222750
EAN	7291050042949
Valid tyre size	700 / 55 - 34
LI / SI / PR	168 A2 / 161 A8, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 346
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	243,96
Recommended rim size	24
Maximum air pressure [bar].	2,40
Section width (mm)	700
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	766
Rolling circumference [mm].	5051
Tread depth (mm)	42,0
Lug width (mm)	96-63
Tyre capacity 75% [ltr.]	530.25
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A2	5600	10		2,40	
161 A8	4625	40		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.