

TYRES

Product group	Tyres
Item number	15222760
Valid tyre size	9.5 - 36
LI / SI / PR	109 A8, 6 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222760
EAN	8903635001560
Valid tyre size	9.5 - 36
LI / SI / PR	109 A8, 6 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	38,16
Recommended rim size	8
Permitted rim size	7
Maximum air pressure [bar].	2,10
Section width (mm)	241
Outer diameter of tyre [mm].	1353
Stat. radius (SLR) [mm]	590
Rolling circumference [mm].	3906
Tread depth (mm)	22,0
Lug width (mm)	37-24
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
109 A8	1030	40		2,10	