

TYRES

Product group	Tyres
Item number	15222783
Valid tyre size	15.5 - 38
LI / SI / PR	133 A8, 8 PR
TL/TT	тт
SET	Tube
Brand	Alliance
Tread pattern	FarmPRO 324



Notes and features

- The Alliance FarmPro 324 has a modern 45 degree lug angle design, suitable for field and road applications.
- In field use, the tyre is characterised by very good traction.
- The revised, new-look tread pattern provides excellent self-cleaning properties.
- Its particularly resistant rubber compound prevents the enlargement of minor punctures.
- The complete R-1 range is available with this tread pattern.



Technical Informations

Item number	15222783
EAN	4040658117084
Valid tyre size	15.5 - 38
LI / SI / PR	133 A8, 8 PR
TL/TT	тт
SET	Tube
Valve designation	TR 218 A
Ventilposition	lateral
Brand	Alliance
Tread pattern	FarmPRO 324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	80,17
Recommended rim size	14L
Maximum air pressure [bar].	1,80
Section width (mm)	394
Outer diameter of tyre [mm].	1569
Stat. radius (SLR) [mm]	737
Rolling circumference [mm].	4813
Tread depth (mm)	28,0
Number of lugs	22x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		1,80	