

TYRES

Product group	Tyres
Item number	15222790
Valid tyre size	12.4 - 38
LI / SI / PR	122 A8, 6 PR
TL/TT	TT
Brand	Alliance
Tread pattern	304



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

Notes and features

- Agricultural bias tyre for use on rear wheel tractors, small tractors and vineyard tractors.
- Double-angled R-1 lugs with large spaces in the tread pattern for good traction and self-cleaning.
- Suitable for sloping terrain and occasional trips on the road.
- Rugged nylon casing.

Technical Informations

Item number	15222790
EAN	8903635000181
Valid tyre size	12.4 - 38
LI / SI / PR	122 A8, 6 PR
TL/TT	TT
Brand	Alliance
Tread pattern	304
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	55,45
Recommended rim size	11
Permitted rim size	10
Maximum air pressure [bar].	1,70
Section width (mm)	315
Outer diameter of tyre [mm].	1515
Stat. radius (SLR) [mm]	710
Rolling circumference [mm].	4576
Tread depth (mm)	30,0
Lug width (mm)	25
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40		1,70	