

TYRES

Product group	Tyres
Item number	15222794
Valid tyre size	13.6 - 38
LI / SI / PR	131 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	304



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

Notes and features

- Agricultural bias tyre for use on rear wheel tractors, small tractors and vineyard tractors.
- Double-angled R-1 lugs with large spaces in the tread pattern for good traction and self-cleaning.
- Suitable for sloping terrain and occasional trips on the road.
- Rugged nylon casing.

Technical Informations

Item number	15222794
EAN	8903635000198
Valid tyre size	13.6 - 38
LI / SI / PR	131 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	304
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	63,47
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	2,00
Section width (mm)	345
Outer diameter of tyre [mm].	1565
Stat. radius (SLR) [mm]	729
Rolling circumference [mm].	4709
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A8	1950	40		2,00	