

TYRES

Product group	Tyres
Item number	15222797
Valid tyre size	16.9 - 38
LI / SI / PR	156 A2 / 149 A8, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 356



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Alliance Forestry 356 is a modern bias tyre for high-power tractors in forestry applications or for heavy-duty operations in agriculture.
- It is also suitable for agricultural vehicles used on construction sites.
- The tyre is characterised by high traction, low slip and low fuel consumption.
- Due to its strong nylon casing with steel belts, high undertread gauge, reinforced sidewalls and a sturdy rubber compound, the tyre is extremely robust and durable.
- The non-skid tread pattern promises high traction, even on compacted or wet surfaces.

Technical Informations

Item number	15222797
EAN	7291050044110
Valid tyre size	16.9 - 38
LI / SI / PR	156 A2 / 149 A8, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 356
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	145,64
Recommended rim size	15
Permitted rim size	14
Maximum air pressure [bar].	2,60
Section width (mm)	429
Outer diameter of tyre [mm].	1675
Stat. radius (SLR) [mm]	772
Rolling circumference [mm].	5007
Tread depth (mm)	45,5
Lug width (mm)	36
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A2	4000	10		2,60	
149 A8	3250	40		2,60	