

TYRES

Product group	Tyres	
Item number	15222798	
Valid tyre size	14.9 - 38	
LI / SI / PR	135 A8, 8 PR	
TL/TT	тт	
Brand	Alliance	
Tread pattern	304	





- Agricultural bias tyre for use on rear wheel tractors, small tractors and vineyard tractors.
- Double-angled R-1 lugs with large spaces in the tread pattern for good traction and self-cleaning.
- Suitable for sloping terrain and occasional trips on the road
- Rugged nylon casing.



Technical Informations

Item number	15222798
EAN	8903635000204
Valid tyre size	14.9 - 38
LI / SI / PR	135 A8, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	304
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	70,29
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	1,80
Section width (mm)	378
Outer diameter of tyre [mm].	1615
Stat. radius (SLR) [mm]	748
Rolling circumference [mm].	4843
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A8	2180	40		1,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.