

## **TYRES**

Product group	Tyres
Item number	15222802
Valid tyre size	16.9 - 38
LI / SI / PR	141 A8, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	FarmPRO 324



## Notes and features

- The Alliance FarmPro 324 has a modern 45 degree lug angle design, suitable for field and road applications.
- In field use, the tyre is characterised by very good traction.
- The revised, new-look tread pattern provides excellent self-cleaning properties.
- Its particularly resistant rubber compound prevents the enlargement of minor punctures.
- The complete R-1 range is available with this tread pattern.



## **Technical Informations**

Item number	15222802
EAN	8903635014799
Valid tyre size	16.9 - 38
LI / SI / PR	141 A8, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	FarmPRO 324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,67
Recommended rim size	15L
Maximum air pressure [bar].	1,70
Section width (mm)	430
Outer diameter of tyre [mm].	1689
Stat. radius (SLR) [mm]	770
Rolling circumference [mm].	5007
Tread depth (mm)	31,6
Number of lugs	21x2
Guarantee period	7 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40		1,70	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.