

TYRES

Product group	Tyres
Item number	15222813
Valid tyre size	600 / 65 - 38
LI / SI / PR	166 A2 / 159 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360



Notes and features

- The Alliance Forestry 360 is a forestry tyre for light forestry applications.
- Its low lug angles provide excellent traction.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls and tread pattern, the tyre is particularly robust.
- The tyre can also be used for agro-industrial applications.

Technical Informations

Item number	15222813
EAN	7291050065191
Valid tyre size	600 / 65 - 38
LI / SI / PR	166 A2 / 159 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	210,69
Recommended rim size	W16L
Permitted rim size	W18L, DW18L, DW20B
Maximum air pressure [bar].	2,40
Section width (mm)	557
Outer diameter of tyre [mm].	1760
Stat. radius (SLR) [mm]	819
Rolling circumference [mm].	5318
Tread depth (mm)	48,0
Number of lugs	23x2
Tyre capacity 75% [litr.]	524
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A2	5300	10		2,40	
159 A8	4375	40		2,40	