# Bohnenkamp Moving Professionals

22.09.2024

#### **TYRES**

Product group	Tyres
Item number	15222840
Valid tyre size	20.8 - 38
LI / SI / PR	159 A8, 14 PR
TL/TT	тт
Brand	Alliance
Tread pattern	347





#### Notes and features

- Bias agricultural wide-base tyre for tractors and harvesters.
- Lugs at a 23° angle allow even the heaviest pulling operations in all kinds of operating conditions.
- Concentrically-overlapping lugs for comfortable handling on the road, even with heavy machinery.
- Reinforced nylon casing provides protection against punctures.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	15222840
EAN	8903635001072
Valid tyre size	20.8 - 38
LI / SI / PR	159 A8, 14 PR
TL/TT	Π
Brand	Alliance
Tread pattern	347
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	157,66
Recommended rim size	18
Maximum air pressure [bar].	2,30
Section width (mm)	528
Outer diameter of tyre [mm].	1840
Stat. radius (SLR) [mm]	826
Rolling circumference [mm].	5411
Tread depth (mm)	41,0
Lug width (mm)	48
Guarantee period	7 years
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		2,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.