Bohnenkamp Moving Professionals

19.09.2024

TYRES

Product group	Tyres	
Item number	15223080	
Valid tyre size	380 / 70 - 28	
LI / SI / PR	145 A2 / 138 A8, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agro Forestry 370	





Notes and features

- The Alliance Agro Forestry 370 of the 70 series was • designed for agricultural tractors used in the forest and on fields.
- The tyre enables combined work in the field and in the forest without any inflation pressure adaptation.
- The tyre structure maintains the high elastic characteristics that enable high traction in the field and low soil compaction.
- At the same time, the strong nylon casing with steel . breakers and the durable rubber compound provide effective damage resistance in forestry applications.
- The Alliance Agro Forestry 370 70 series was developed • for tractors working simultaneously in forests and fields.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15223080
EAN	7291050046299
Valid tyre size	380 / 70 - 28
LI / SI / PR	145 A2 / 138 A8, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Forestry 370
TRA Code	R1-W
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	98,18
Recommended rim size	12
Permitted rim size	11, 13
Maximum air pressure [bar].	3,00
Section width (mm)	380
Outer diameter of tyre [mm].	1308
Stat. radius (SLR) [mm]	609
Rolling circumference [mm].	3935
Tread depth (mm)	36,0
Lug width (mm)	45-33
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A2	2900	10		3,00	
138 A8	2360	40		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.