

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15223200 |
| Valid tyre size | 520 / 70 - 38 |
| LI / SI / PR | 162 A2 / 155 A8, 14 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agro Forestry 370 |



Notes and features

- The Alliance Agro Forestry 370 of the 70 series was designed for agricultural tractors used in the forest and on fields.
- The tyre enables combined work in the field and in the forest without any inflation pressure adaptation.
- The tyre structure maintains the high elastic characteristics that enable high traction in the field and low soil compaction.
- At the same time, the strong nylon casing with steel breakers and the durable rubber compound provide effective damage resistance in forestry applications.
- The Alliance Agro Forestry 370 70 series was developed for tractors working simultaneously in forests and fields.

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15223200 |
| EAN | 7291050046350 |
| Valid tyre size | 520 / 70 - 38 |
| LI / SI / PR | 162 A2 / 155 A8, 14 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agro Forestry 370 |
| TRA Code | R1-W |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 181,88 |
| Recommended rim size | 16 |
| Permitted rim size | 18 |
| Maximum air pressure [bar]. | 2,50 |
| Section width (mm) | 520 |
| Outer diameter of tyre [mm]. | 1758 |
| Stat. radius (SLR) [mm] | 819 |
| Rolling circumference [mm]. | 5292 |
| Tread depth (mm) | 54,0 |
| Lug width (mm) | 63-44 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 162 A2 | 4750 | 10 | | 2,50 | |
| 155 A8 | 3875 | 40 | | 2,50 | |