

TYRES

Product group	Tyres	
Item number	15223347	
Valid tyre size	420 / 85 - 38	
LI / SI / PR	149 A8 / 146 B, 14 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agro Forestry 333	





Notes and features

- The Alliance Agro Forestry 333 is a newly-developed 85 series steel belted forestry tyre for tractors used in forestry.
- The tyre is characterised by good grip, high traction, low slip and low fuel consumption.
- Due to its extra-large contact area, large tread depth and cut- and puncture-resistant rubber compound, the tyre is very sturdy and durable.
- The solid bead core and reinforced sidewalls with a high ply turn-up in the bead area ensure excellent stability and puncture protection.
- The lugs are 25% higher than on standard R-1 tyres and provide high traction even on wet soil.



Technical Informations

Item number	15223347
EAN	8903635012221
Valid tyre size	420 / 85 - 38
LI / SI / PR	149 A8 / 146 B, 14 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Forestry 333
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	155,17
Recommended rim size	15
Permitted rim size	13, 14
Maximum air pressure [bar].	2,40
Section width (mm)	430
Outer diameter of tyre [mm].	1680
Stat. radius (SLR) [mm]	774
Rolling circumference [mm].	5021
Tread depth (mm)	49,0
Number of lugs	20x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		2,40	
146 B	3000	50		2,40	