

TYRES

| | |
|-----------------|-----------------------|
| Product group | Tyres |
| Item number | 15223350 |
| Valid tyre size | 460 / 85 - 38 |
| LI / SI / PR | 154 A8 / 151 B, 14 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agro Forestry 333 |



Notes and features

- The Alliance Agro Forestry 333 is a newly-developed 85 series steel belted forestry tyre for tractors used in forestry.
- The tyre is characterised by good grip, high traction, low slip and low fuel consumption.
- Due to its extra-large contact area, large tread depth and cut- and puncture-resistant rubber compound, the tyre is very sturdy and durable.
- The solid bead core and reinforced sidewalls with a high ply turn-up in the bead area ensure excellent stability and puncture protection.
- The lugs are 25% higher than on standard R-1 tyres and provide high traction even on wet soil.

Technical Informations

| | |
|------------------------------|-----------------------|
| Item number | 15223350 |
| EAN | 8903635010128 |
| Valid tyre size | 460 / 85 - 38 |
| LI / SI / PR | 154 A8 / 151 B, 14 PR |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agro Forestry 333 |
| TRA Code | R1-W |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 176,78 |
| Recommended rim size | 16 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 460 |
| Outer diameter of tyre [mm]. | 1747 |
| Stat. radius (SLR) [mm] | 801 |
| Rolling circumference [mm]. | 5206 |
| Tread depth (mm) | 53,0 |
| Number of lugs | 21x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 154 A8 | 3750 | 40 | | 2,40 | |
| 151 B | 3450 | 50 | | 2,40 | |