

TYRES

Product group	Tyres
Item number	15224282
Valid tyre size	12.4 R 36
LI / SI / PR	146 A8 / 143 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Agricultural standard tyre of the 85/80 series for tractors in the medium power range up to approx. 180 hp.
- Many dimensions can also be used as a row crop tyre.
- Excellent traction for low fuel consumption.
- Low soil compaction and improved ride comfort.
- Tread pattern depth increased by 10-15 % compared with a standard R-1 tyre for a long service life.

Technical Informations

Item number	15224282
EAN	7291050048484
Valid tyre size	12.4 R 36
LI / SI / PR	146 A8 / 143 B
TL/TT	TL
Brand	Alliance
Tread pattern	Power Drive 356
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	77,28
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	3,80
Section width (mm)	315
Outer diameter of tyre [mm].	1450
Stat. radius (SLR) [mm]	680
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4507
Tyre capacity 75% [ltr.]	158.25
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A8	3000	40		3,80	
143 B	2725	50		3,80	