Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15225087	
Valid tyre size	IF 520 / 80 R 26 CFO	
LI / SI / PR	165 A8	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 372	



Notes and features

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number 15225087 EAN 7291050069212 Valid tyre size IF 520 / 80 R 26 CFO LI / SI / PR 165 A8 TL/TT TL Brand Alliance	
Valid tyre size IF 520 / 80 R 26 CFO LI / SI / PR 165 A8 TL/TT TL	
LI / SI / PR 165 A8 TL/TT TL	
TL/TT TL	
Brand Alliance	
Tread pattern Agriflex 372	
Carcass properties Steel Belted	
Antistatic No	
Tyre colour Black	
ECE regulation number ECE 106	
Nettogewicht [kg] (gültig) 155,99	
Recommended rim size 16	
Maximum air pressure [bar]. 3,20	
Section width (mm) 505	
Outer diameter of tyre [mm]. 1465	
Stat. radius (SLR) [mm] 651	
Rolling circumference [mm]. 4372	
Tyre capacity 75% [ltr.] 355.5	
Guarantee period 10 years	
E-Ready No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A8	5150	40		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.