

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 15225106 |
| Valid tyre size | 480 / 65 R 28 |
| LI / SI / PR | 145 A8 / 142 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agristar 365 |





Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.



Technical Informations

| Item number | 15225106 |
|------------------------------|----------------|
| EAN | 8903635017103 |
| Valid tyre size | 480 / 65 R 28 |
| LI / SI / PR | 145 A8 / 142 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agristar 365 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 98,87 |
| Recommended rim size | 15 |
| Permitted rim size | 14 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 484 |
| Outer diameter of tyre [mm]. | 1335 |
| Stat. radius (SLR) [mm] | 624 |
| Speed Radius Index (SRI) | 650 |
| Rolling circumference [mm]. | 4094 |
| Tread depth (mm) | 40,0 |
| Tyre capacity 75% [ltr.] | 229 |
| Guarantee period | 7 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 145 A8 | 2900 | 40 | | 2,40 | |
| 142 D | 2650 | 65 | | 2,40 | |