

TYRES

Product group	Tyres
Item number	15225112
Valid tyre size	480 / 70 R 28
LI / SI / PR	151 A8 / 145 E
TL/TT	TL
Brand	Alliance
Tread pattern	370





Notes and features

- Agricultural wide-base tyre of the 70 series for tractors in the low-performance range up to large tractors with over 200 hp.
- All-round tyre for use on farmland and grassland.
- Offers higher load capacities with the same inflation pressure in comparison to 85 standard tyres.
- R-1W drive tread pattern with higher tread depth for improved traction and high mileage.



Technical Informations

Item number	15225112
EAN	7291050021203
Valid tyre size	480 / 70 R 28
LI / SI / PR	151 A8 / 145 E
TL/TT	TL
Brand	Alliance
Tread pattern	370
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	106,82
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	2,50
Section width (mm)	479
Outer diameter of tyre [mm].	1423
Stat. radius (SLR) [mm]	640
Rolling circumference [mm].	4313
Tread depth (mm)	46,0
Number of lugs	20x2
Lug width (mm)	37
Tyre capacity 75% [ltr.]	288
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		2,50	
145 E	2900	70		2,50	